

**LBSP
AS/AL**

Being mini-sized, light weight, high efficiency, good reliability and so on. In special, it has the remote control and UPS function



Features

- Compact design, small size and light weight
- Internal EMI filter
- Remote Control Function
- Short-circuit protection and over-load protection
- Certificate : CE Certificate
- High efficiency and good reliability
- Power Output LED Indicator
- Over-heat Protection
- UPS Function

Property Parameters

Type	LBSP -1312AS	LBSP-1324AS	LBSP-1305AL
Output Voltage	12 V	24 V	5 V
Output Current	3 A	1.5 A	10 A
Dimensions(LxWxH)	71mm×106mm×65mm		126mm×106mm×65mm
Installation	Standard 35 mm D		IN (EN50022-35)
Full-range Voltaje Input	100-240VAC/140-340VDC		
Waving Voltaje Allowance Range	85-264VAC/120-370VDC		
Input Frequency	47-63Hz		
Output Voltaje Stability	≤±0.5%		
Ripple	≤150mVp-p		
Temperatura	-25°C ~ +70°C		
Insulation and Breakdown	>1.5KV		
Efficiency	>75%		

info@logicbus.com.mx www.logicbus.com.mx

Alcalde # 1822 Col. Miraflores C.P. 44270 Guadalajara, Jal.
MX 01 (33) 3854-5975 y 3823-4349 USA 001 (619)- 884-94-93 (San Diego, CA. Office)