

USB to 2-Port RS-232, RS-422, RS-485 DB9 Serial Interface Adapter

Part: 2203 Model: SeaLINK+2



Teléfonos / Phone number

Mex: +52 (33)-3854-5975
+52 (33)-3823-4349
USA: +1 (619) 619-7350

Página Web / Website

tienda.logicbus.com.mx
logicbus.com

Correo electrónico / E-mail

ventas@logicbus.com
sales@logicbus.com



Dirección / Address



Av. Fray Antonio Alcalde 1822
Miraflores, 44270
Guadalajara, Jal



8280 Clairemont Mesa Blvd
Suite 122
San Diego, CA 92111



Description

The SeaLINK® 2203 USB serial I/O adapter provides two RS-232, RS-422, or RS-485 serial ports for USB connectivity to legacy or non-USB compliant serial devices. Each port is individually configurable for RS-232, RS-422, or RS-485.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Microsoft Windows operating systems. After installing the software, simply connect the 2203 serial interface adapter to your USB port. The device is immediately recognized by the system. Now your non-USB serial peripherals can have the same connection simplicity and ease of use as USB aware peripherals.

Do you know that adapter design can impact your application? Find out how in this USB Serial performance report.

Category: Two Port

Additional information

Family	SeaLINK
Communications Chip	USB/UART
Dimensions	7.1 (L) x 5.3 (W) x 1.5 (H)
Electrical Interface	RS-232, RS-422, RS-485
High Retention USB	Yes
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB
Max Data Distance	4000 feet
Max Data Rate	921.6K bps
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	2
Power Requirement	+5V @ 500mA
RoHS Compliant	Yes
Serial Connector(s)	DB9M
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Powered	Yes

USB Specification

1.1 Compliant
2.0 Compatible

Compliant with RoHS and WEEE directives

Each port individually configurable for RS-232, RS-422, or RS-485

High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO

Data rates to 921.6K bps

Automatic RS-485 enable/disable

Serial and USB activity LEDs

Hot-swappable

Powered by USB connection

Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems

DB-9M connectors

Includes 6' USB device cable (Item# [CA179](#))

Copyright 1996 - 2021 - Sealevel Systems, Inc. All rights reserved.