

USB to 8-Port RS-232, RS-485 RJ45 VersaCom Serial Interface Adapter



Part: 2807 **Model:** SeaLINK+8.VC

Teléfonos / Phone number

Mex: +52 (33)-3854-5975
+52 (33)-3823-4349
USA: +1 (619) 619-7350

Página Web / Website

tienda.logicbus.com.mx
logicbus.com

Correo electrónico / E-mail

ventas@logicbus.com
sales@logicbus.com



Dirección / Address



Av. Fray Antonio Alcalde 1822
Miraflores, 44270
Guadalajara, Jal



8280 Clairemont Mesa Blvd
Suite 122
San Diego, CA 92111



Description

The SeaLINK® 2807 8-port USB to serial adapter offers an easy way to connect multiple RS-232 or RS-485 devices via a single USB port. With the unique VersaCom multi-interface connector design included on the 2807, both RS-232 and two-wire RS-485 signals are always present and active on the RJ45 serial connectors. Simply select the appropriate pin out for RS-232 or two-wire RS-485 on each individual port. There is never a need to open the enclosure to set internal jumpers or switches, so field installation and service is easy. Status LEDs display transmit and receive data activity.

Sealevel's [SeaCOM](#) USB software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. After installing the software, the serial ports appear as standard COM ports to the host system enabling compatibility with legacy software. The 2807 uses a state machine architecture that greatly reduces the host computer's overhead when communicating over multiple ports simultaneously. Data rates up to 921.6K bps are supported.

The 2807 is USB bus-powered, so no external power supply is required. For conveniently powering serial peripherals, ordering options allow an external power source to be connected to a DC jack on the rear of the unit. The supplied power is fused and connected to pin 5 on each of the eight RJ45 connectors. Select the appropriate configuration option for your application. Optional power supplies are available under the Accessories tab.

To further simplify connecting to VersaCom RJ45 connectors, Sealevel offers a number of accessories including RJ45 modular adapters. With these helpful adapters you can easily connect to serial ports on virtually any computer, PLC, or peripheral regardless of the device's serial connector type or gender. For more information please browse our full line of adapters and converters.

Do you know that adapter design can impact your application? Find out how in this [USB Serial performance](#)

report. Category: [Eight](#)

[Port](#)

Additional information

Operating Temperature	0°C to 70°C (32°F to 158°F)
Communications Chip	USB/UART
Dimensions	9.2 (L) x 5.3 (W) x 1.7 (H)
Electrical Interface	RS-232
High Retention USB	Yes
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB
Max Data Distance	50 feet (RS-232)4000 feet (RS-485)
Max Data Rate	921.6K bps

USB Specification	1.1 Compliant 2.0 Compatible
Family	SeaLINK
Power Requirement	+5V @ 500mA
RoHS Compliant	Yes
Serial Connector(s)	RJ45, VersaCom
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Powered	Yes
# of Ports	8

Compliant with RoHS and WEEE directives

Utilizes high-speed UARTs with 128-byte Tx FIFOs and 384-byte Rx FIFOs

Housed in rugged, attractive plastic enclosure

Powered by USB connection

Optionally configured to power 5, 12 or 24 VDC serial peripherals

Optional external power is internally fused and connected to pin 5 on each RJ45 connector

Provides 8 RJ45 serial ports with Tx/Rx status LEDs

Integrates transmit and receive LED indicators on each port

VersaCom design allows RS-232 or two-wire RS-485 selection via cabling on each individual port

High-retention USB type B connector prevents accidental disconnection of USB cable

Sealevel software supports Windows and Linux operating systems

Includes 72-inch USB cable (Item# [CA179](#))

Copyright 1996 - 2021 - Sealevel Systems, Inc. All rights reserved.