

USB to 1-Port Isolated RS-232 DB25 Serial Interface Adapter



Part: 2103 **Model:** SeaLINK+232I

tienda.logicbus.com.mx
logicbus.com

ventas@logicbus.com
sales@logicbus.com

México
+52 (33)-3854-5975

USA
+1 (619) 619-7350

Need some help? [Contact us](#)

Description

The 2103 USB isolated serial I/O adapter provides a single USB to RS-232 serial port allowing USB connectivity to legacy and non-USB compliant devices. Now your non-USB peripherals can have the same connection simplicity and ease of use as USB peripherals. The serial interface adapter provides isolation to help prevent damage caused by ground loops and surges. Power for the SeaLINK+232I serial interface adapter is obtained directly from the USB cable, eliminating the need for external power supplies.

Sealevel's [SeaCOM](#) USB software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. After installing the software, simply connect the SeaLINK® serial interface adapter to your USB port and the device is immediately recognized by the system as a standard serial port.

Do you know that adapter design can impact your application? Find out how in this [USB Serial](#) performance report.

Category: [One Port](#)

Additional information

Family	SeaLINK
Communications Chip	USB/UART
Dimensions	3.8" (L) x 2.3" (W) x 1.0" (H) 9.66 cm (L) x 5.84 cm (W) x 2.54 cm (H)
Electrical Interface	RS-232
High Retention USB	Yes
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB

Max Data Distance	50 feet
Max Data Rate	460.8K bps
Optically Isolated	Yes
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	1
Power Requirement	+5V @ 100mA
RoHS Compliant	Yes
Serial Connector(s)	DB25M
Storage Temperature	0°C to 70°C (32°F to 158°F)
USB Powered	Yes
USB Specification	1.1 Compliant 2.0 Compatible

Compliant with RoHS and WEEE directives

High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO

Optical isolation provides protection against transients and ground loops

Data rates to 460.8K bps

Hot-swappable

Powered by USB connection

Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems

DB-25M connector

Includes 6' USB device cable (Item# [CA179](#))